



N.O. Isolated Relay Output 16 Pts (36 Pin)



- Variety of voltages
- 8 to 32 points per module
- Isolated and nonisolated module types
- Point-level output fault states
- Direct-connect or rack-optimized communication
- Field-side diagnostics on select modules

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	ControlLogix (Bul. 1756 / 1757)
Component Type PLC & I/O	Relay Output Module
Module Specific Functions	ControlLogix AC (10...240V) DC (5...125V) isolated contact module, 16 N.O. individually isolated
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Vibration Acceleration (Max.)	2 m/s ²
Vibration Frequency, Operational (Max.)	500 Hz
Standards Compliance	IEEE C37.90.1 IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-27 IEC 60068-2-30 IEC 60068-2-6 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-6-4
Certifications	CE CSA C-Tick FM KC (KCC) UL

Catalogue No: **1756-OW16I**

CONTROLLOGIX 16DO ISOLATED RELAY MODULE

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® I/O Modules > ControlLogix® Digital I/O Modules



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -