Catalogue No: **SFBWP2LEDP**

PLATINUM RANGE SURFACE MOUNT SPITFIRE W/P EM D63 COB LED

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Spitfire EM

Representative Photo Only
(actual product may vary based on configuration selections)

Platinum Spitfire Dual LED Weather Proof Surface Mount

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

SPECIFICATIONS	
Component Type Emergency Lighting	Spitfire
Testing System	Single Point Unit
Operating Mode	Non-Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	1.0 W
Mounting	Surface - Ceilling
LED Life	100,000 hours
Photometric Classification	C0:D63 C90:D63
Battery Type	LiFePO4
Height	130 mm
Width	188 mm
Depth	278 mm
Base Colour	Grey
Battery Replacement	0301303P
IP Rating	IP67
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	Spitfire Weatherproof Emergency, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	Platinum Spitfire LED Weatherproof Non-maintained_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-